

Felt Wheels

Eisinger presents Paramount® felt wheels made from 100% fine wool felt and manufactured to assure even density throughout the wheel. Harder densities (hard, rock hard and flint hard) are used with Greystar to create a smooth, flat finish with sharp edges. Softer densities (soft and medium) can be used with rouge to produce a high shine.

Standard Felt Wheels

All wheels are supplied with a pin hole for easy mounting on a tapered spindle.

Wheel Dimensions	Soft	Medium	Hard	Rock Hard	Flint Hard	Ship Weight Per Dozen
1/4" x 1/4" (13 x 3mm)	46-001-1	-	46-001-3	-	-	1/4lb (100g)
3/4" x 1/4" (19 x 3mm)	46-006-1	-	46-006-3	-	-	1/4lb (100g)
1" x 1/4" (25 x 3mm)	46-011-1	46-011-2	46-011-3	-	-	1/4lb (225g)
1" x 3/4" (25 x 6mm)	-	-	46-012-3	-	-	1/4lb (225g)
3" x 1/4" (76 x 13mm)	46-039-1	46-039-2	46-039-3	46-039-4	-	1 1/4lbs (675g)
4" x 1/4" (102 x 6mm)	46-042-1	46-042-2	46-042-3	46-042-4	46-042-5	3lbs (1.25kg)
4" x 1/4" (102 x 13mm)	46-044-1	46-044-2	46-044-3	46-044-4	46-044-5	5lbs (2.5kg)
6" x 1/4" (152 x 6mm)	46-052-1	46-052-2	46-052-3	46-052-4	46-052-5	7lbs (3.25kg)
6" x 1/4" (152 x 13mm)	46-054-1	46-054-2	46-054-3	46-054-4	46-054-5	10lbs (4.5kg)
6" x 1" (152 x 25mm)	46-056-1	46-056-2	46-056-3	46-056-4	46-056-5	17lbs (7.75kg)
7" x 1/4" (178 x 13mm)	46-059-1	46-059-2	46-059-3	46-059-4	46-059-5	13lbs (6kg)
8" x 1/4" (203 x 13mm)	46-064-1	46-064-2	46-064-3	46-064-4	46-064-5	17lbs (7.75kg)



Bevelled and Split Lapping Felt Wheels

To be used on our Lapping Machines (see page 95). Slits allow for easy viewing of the jewelry while working. All wheels come with pin holes for mounting directly on a left hand tapered spindle. All wheels are with four slits.

Wheel Dimensions	Medium	Hard	Rock Hard	Flint Hard	Ship Wt Per Wheel
4" x 1/4" (102 x 13mm)	46-244-2	46-244-3	46-244-4	46-254-5	3/4lb (339g)
6" x 1/4" (152 x 13mm)		46-254-2	46-254-3	46-254-4	1lb (450g)
7" x 1/4" (178 x 13mm)		46-259-2	46-259-3	46-259-4	1 1/4lb (675g)
8" x 1/4" (203 x 13mm)	46-266-2	46-266-3	46-266-4	46-266-5	2lbs (1kg)



Knife Edge Felt Wheels

Are hard for extra firmness to reach into narrow spaces. All wheels have pin hole centers.

Diameter	Ship Wt Per Dozen	Order #
1/4" (13mm)	1/4lb (113g)	46-102
3/4" (16mm)	1/4lb (113g)	46-103
1/2" (19mm)	1/4lb (113g)	46-104
1" (25mm)	3/4lb (150g)	46-105
1 1/4" (38mm)	1lb (450g)	46-106
2" (51mm)	1lb (450g)	46-107
2 1/4" (64mm)	2lbs (1kg)	46-108
3" (76mm)	2lbs (1kg)	46-109
4" (102mm)	4lbs (2kg)	46-110



StarLeaf Felt Ring Buffs

Finest quality felt mounted on reinforced hardwood. Slightly tapered wood mandrel screws directly on a tapered spindle. Available in regular and firm. Also available are solid felt which mount directly on shaft. Measure Felt Only.



Felt Length	Ring	Order # Regular	Order # Firm	Order # Solid	Ship Wt Per Dozen
2 1/4" (73mm)	Child	46-422-2			1lb (450g)
3" (76mm)	Ladies	46-423-2	46-423-3	46-433-2	1lb (450g)
4" (102mm)	Ladies	46-424-2	46-424-3	46-434-2	1 1/4lbs (750g)
5" (127mm)	Men	46-425-2	46-425-3		2lbs (900g)



StarLeaf Felt Cones

Tapered for hard to reach areas.

Diameter	Length	Ship Wt Per Dozen	Order #
1/4" (6mm)	1/4" (12.5mm)	1/4lb (100g)	46-401
3/4" (9.5mm)	3/4" (19mm)	1/4lb (100g)	46-402
1/2" (12.5mm)	1" (25mm)	1/4lb (100g)	46-403
3/4" (19mm)	1 1/4" (38mm)	6oz (150g)	46-404
1" (25mm)	2" (51mm)	10oz (280g)	46-405



Mounted Felt Bobs

46-420
Convenient kit of 5 popular shapes. 3/4" (2.35mm) shank.

String Ring Buff

46-450

Unique design popular in Europe. Used to polish inside rings and to reach into inaccessible areas. 3 1/4" (89mm) length. Shipping weight: 1 1/4lbs (750g) per dozen.



Felt Wheel Truing Stone

48-016

Extra fine stone is ideal for restoring a flat edge to a worn felt wheel. Combination stone has two grits of silicon carbide. Shipping weight: 1/4lb (225g)

