



The Jun-Air Compressor

50-010

Uniquely designed compressor that runs as quiet as a refrigerator. These low maintenance units are ideal when noise is a problem. Centrifugal oil circulation ensures efficient lubrication under all temperature conditions with the glass oil window making regular oil level checks simple. All other components are well protected.

Jun-Air is a complete air-compressor, provided with a relay switch, motor protector, adjustable automatic stop/start pressure switch, air receiver with safety valve, gauge, drain cock and filter/regulator. Extra large storage tank accommodates production use.

Features:

- Exceptionally quiet
- Easy to operate
- Low in electrical consumption
- Minimal maintenance
- Easily portable
- 2 year guarantee
- Anti-corrosion treated

SPECIFICATIONS:

Tank capacity: 6 1/4 gallons
 CFM@120psi: 2.12
 Dimensions: 20 1/4" w x 14 3/4" d x 14 3/4" h (547 x 374 x 374mm)
 Energy: 115V, 5.4 amps, 1/4hp
 Shipping weight: 67lbs (30.5kg)



Silentaire Compressor

50-011

This quality built and highly efficient 1/4hp compressor will perform to your full satisfaction for many years.

SPECIFICATIONS:

Capacity: 6 gallon
 CFM: 2.15 free air@84-114 psi
 Energy: 110V, 60hz
 Shipping weight: 68lbs (32kg)

Dessiccant Filters

Desiccant granules absorbs the excess moisture that builds up in air supply lines. Desiccant changes from blue to pink when saturated. Can be dried in an oven and reused.

- 11-053 - Regular For 1 or 2 wax injectors
- 11-053-1 - 1lb refill
- 11-054 - Large For up to 6 wax injectors.
- 11-054-1 - 3lb refill



Oxygen Generator

Cuts your oxygen costs by 95%. By using a new process called Pressure Swing Absorption, oxygen is separated from room air. These machines eliminate the expense and hassle of handling oxygen tanks. They require little maintenance and are easily installed. Sizes AS-20 and AS-45 require a compressor. All units run off of 110V, 60hz (available in 220V). For higher volume a 60 gallon (228L) storage tank can be added to the system.



Model	Equivalent Tank Usage per Week	Dimensions	Order#	Ship wt
AS-12	1.5	13" w x 12" d x 25" h (330 x 280 x 610mm)	50-210	60lbs (28kg)
AS-20	3*	13" w x 11" d x 56 1/4" h (330 x 269 x 1473mm)	50-220	265lbs (120.5kg)
AS-45	7*	17" w x 15" d x 58" h (432 x 381 x 1545mm)	50-245	369lbs (167.5kg)
60Gal (228L) Tank		24" dia x 65" h (610 x 1651mm)	50-250	170lbs (77.3kg)

Deltech Refrigerated Compressed Air Dryers

Uses refrigeration to chill the air and then filters the solidified moisture.

HX 10 A- 11-050

Provides consistent air drying performance to handle 10 wax injectors or more.

SPECIFICATIONS:

Dimensions: 20" w x 17 1/4" d x 17 1/4" h (508 x 420 x 420mm)
 Energy: 110V, 2 amps
 Shipping weight: 85lbs (39kg)

HX 50 - 11-051

Will handle 18 to 24 wax injectors.

SPECIFICATIONS:

Dimensions: 24 1/4" w x 24 1/4" d x 20 1/4" h (644 x 644 x 514mm)
 Energy: 110V, 2 amps
 Shipping weight: 145lbs (65.5kg)



Oiler-Filter Regulator

51-141-09

All air tools require protection from the moisture found in air lines from compressors as well as needing constant lubrication. Our all-in-one assembly includes a regulator to control air pressure near the tool being used, a built-in dispenser for oil and a filter for condensed water from the air lines. 1/4"(6.3mm) NPT.

